



Product information

REV2013344

Stuffing-Box-Packing Type 2200

Material composition

Diagonally braided from high quality pure carbon fibre yarn, impregnated with graphite and a corrosion inhibitor.

Please note: the colour of the actual product might vary from the above image on this data-sheet.

Properties

TEADIT style 2200 lacks the usual stiffness of conventional carbon packings. Good flexibility and heat dissipating properties, very low coefficient of friction.

Excellent chemical and thermal stability.

Style 2200 is very well suited as top and end rings in combination with styles 2000 and 2010. It prevents gap-extrusion of the softer flexible graphite.

Application areas

Can be used equally well in pumps, also boiler feed pumps, valves, mixers, refiners, etc. in many different industries like pulp- and paper, power stations, chemical and pharmaceutical industry and many more.

Application media

TEADIT style 2200 covers the full pH-range and can be used with nearly all media: cold and hot water, steam, chemicals, hot gases, alcohol, solvents, heat transfer agents, etc.

Not suitable for

Highly concentrated corrosive acids

Benefits

Because style 2200 is a very affordable high quality all-round packing, many companies have standardized on it. Because its coefficient of thermal expansion is very similar to that of steel it needs less adjustments of the gland. Low coefficient of friction means low shaft wear. Its low specific gravity results in excellent economy. Style 2200 closes the gap (also price-wise) between conventional packings and pure graphite packings.



Temperature:

	- temp	+ temp	steam:
(°C)	240	450	650

Pressure:

	rotating:	reciprocating:	static:
(bar)	25	100	300

pH: 0-14

density: 1,1

v: (m/s) 20



STOCKED, SUPPORTED AND DISTRIBUTED BY

email: sales@williamjohnston.co.uk

www.williamjohnston.co.uk



WILLIAM JOHNSTON
& COMPANY LIMITED

Glasgow: 0141 620 1666

Inverness: 01463 238673

Disclaimer

Please note, failure to select the correct materials or products we supply ("the Products") may result in damage to plant, equipment or property. In some instances, it may cause death or personal injury. We are not designers and do not give advice about design related matters concerning the Products. We can help and assist with the technical specifications for the Products. In specific applications, particularly where critical conditions exist, we will try to assist you within the limitations of the services that we offer. All information supplied by us is intended as technical co-operation outlining the specifications of the different Products which we supply. To the extent permitted in law, no warranty is given in respect of any information supplied by us. The customer must satisfy themselves as to the suitability of the Products for their intended application and use. The correct fitting of Products is the responsibility of the customer. Your statutory rights remain unaffected. Save in respect of death, personal injury or fraud, our entire liability to you, however arising from the supply of Products shall be limited to the £10M indemnity amount provided by our insurers.