



## Product information

REV2013344

# Stuffing-Box-Packing Type 2026

### Material composition

Diagonally braided from textured glass-fibre yarn, impregnated throughout with PTFE-dispersion and a silicone-free break-in lubricant.

Please note: the colour of the actual product might vary from the image on this data-sheet.

### Properties

Very dense and supple packing, good chemical resistance.

### Application areas

TEADIT style 2026 is recommended for use in rotary and reciprocating pumps, valves, mixers and agitators etc. in the pulp- and paper, petroleum, chemical and food industry. Also suitable for sugar mills and water treatment plants.

### Application media

Style 2026 can be used with water, steam, solvents, oils, most chemicals, mild acids and lyes, etc.

### Not suitable for

Concentrated acids and lyes, oxygen.

### Benefits

Style 2026 is a multi-service packing suitable for a wide variety of applications throughout a plant.



Temperature:

	- temp	+ temp
(°C)	40	280

Pressure:

	rotating:	reciprocating:	static:
(bar)	15	20	150

pH: 3-12

density: 2

v: (m/s) 8



STOCKED, SUPPORTED AND DISTRIBUTED BY

email: [sales@williamjohnston.co.uk](mailto:sales@williamjohnston.co.uk)

[www.williamjohnston.co.uk](http://www.williamjohnston.co.uk)



**WILLIAM JOHNSTON**  
& COMPANY LIMITED

Glasgow: 0141 620 1666

Inverness: 01463 238673

#### Disclaimer

Please note, failure to select the correct materials or products we supply ("the Products") may result in damage to plant, equipment or property. In some instances, it may cause death or personal injury. We are not designers and do not give advice about design related matters concerning the Products. We can help and assist with the technical specifications for the Products. In specific applications, particularly where critical conditions exist, we will try to assist you within the limitations of the services that we offer. All information supplied by us is intended as technical co-operation outlining the specifications of the different Products which we supply. To the extent permitted in law, no warranty is given in respect of any information supplied by us. The customer must satisfy themselves as to the suitability of the Products for their intended application and use. The correct fitting of Products is the responsibility of the customer. Your statutory rights remain unaffected. Save in respect of death, personal injury or fraud, our entire liability to you, however arising from the supply of Products shall be limited to the £10M indemnity amount provided by our insurers.