

JAMPAK 26

Material composition:

The injectable **TEADIT® JAMPAK 26** sealant is made up from a mixture of high-grade synthetic fibers and a balanced compound of different oils, greases and binders. It is this special combination of fibers and binders which makes nearly leak free operation possible. **TEADIT® JAMPAK 26** is not contaminating and physiologically harmless, the lubricants are FDA conform for use with foodstuff and "clean" applications.

Please note: the colour of the actual product might vary from the above image on this data-sheet.

Technical data:

- pH: 0-14
- V m/s: 12
- Max. temperature: 260°C
- Recommended anti-extrusion-rings: 2006/2060

Application areas:

JAMPAK® 26 can be used with rotating equipment like pumps, pulpers, mixers, etc., but also in piston pumps and valves.

Properties:

TEADIT® JAMPAK 26 is a malleable sealant which can be re-injected during operation, i.e. without having to interrupt the production process. This is in contrast to conventional packings and mechanical seals. Because of the extremely low coefficient of friction of the malleable JAMPAK sealant, it does not depend on flush water or extensive leakage for cooling or lubrication. This reduces frictional heat - which often causes problems for conventional packings rings - this makes the system run cooler, avoids shaft scoring and can effectively reduce energy costs and down time.



Advantages:

- Considerably less down time
- Longer working intervals of pump, because additional packing compound may be injected during operation
- Less leakage (zero (visible) leakage is almost possible)
- No flush water necessary. This saves on water and waste-water
- Hardly any shaft or sleeve wear
- Less maintenance effort - less maintenance cost
- Saves on energy due to less friction on shaft
- No sudden breakdown of pump due to packing or seal failure, because additional packing compound can be injected during operation



STOCKED, SUPPORTED AND DISTRIBUTED BY

email: sales@williamjohnston.co.uk

www.williamjohnston.co.uk



**WILLIAM JOHNSTON
& COMPANY LIMITED**

Glasgow: 0141 620 1666

Inverness: 01463 238673

Disclaimer

Please note, failure to select the correct materials or products we supply ("the Products") may result in damage to plant, equipment or property. In some instances, it may cause death or personal injury. We are not designers and do not give advice about design related matters concerning the Products. We can help and assist with the technical specifications for the Products. In specific applications, particularly where critical conditions exist, we will try to assist you within the limitations of the services that we offer. All information supplied by us is intended as technical co-operation outlining the specifications of the different Products which we supply. To the extent permitted in law, no warranty is given in respect of any information supplied by us. The customer must satisfy themselves as to the suitability of the Products for their intended application and use. The correct fitting of Products is the responsibility of the customer. Your statutory rights remain unaffected. Save in respect of death, personal injury or fraud, our entire liability to you, however arising from the supply of Products shall be limited to the £10M indemnity amount provided by our insurers.