Email: sales@williamjohnston.co.uk

www.williamjohnston.co.uk



Glasgow Tel: +44 (0) 141 620 1666 sales@williamjohnston.co.uk verness Tel: +44 (0) 1463 238 673 www.williamjohnston.co.uk



Product information

Stuffing-Box-Packing Type 2235

REV202111

Description

The new TEADIT packing style 2235 is made from layers of flexible graphite tape plied into compact strands; each individual filament is reinforced with an Inconel® wire jacket. This yarn is then square braided to form a dense yet malleable packing, which is subsequently treated with lubricating agents to reduce stem friction and a corrosion inhibitor to prevent pitting. (® Inconel is a registered trademark of International Co.)

Properties

TEADIT style 2235 is a high-performance valve packing, especially designed for high-pressure, high-temperature steam service. It is self-lubricating, non-hardening, dimensionally stable and easy to install. The Inconel wire mesh covering makes this packing highly resistant to extrusion, the advanced construction assures superior leakage control and highest integrity in steam service.

Application areas

Typical applications for style 2235 include control and block valves, as well as other demanding applications in power plants, refineries and similar industries where high pressures and high temperatures are prevailing.

Application media

Designed for steam applications, **TEADIT style 2235 can also be used with most chemicals and gases.**

Not suitable for

Highly oxidizing agents at high temperature.

Benefits

High mechanical and thermal stability; chemically inert within pH range 0 - 14; quick and easy to install; suitable for rotary and rising-stem valves; low friction, special lubricating system; corrosion inhibitor.

FIRE - SAFE CERTIFICATE





Temperature:

- temp + temp steam: (°C) 240 450 650

Pressure:

rotating: reciprocating: static: (bar) 450

pH: 0 - 14 density: (g/cm^3) 1,6 v: (m/s) < 1

Approval:

• Fire Safe

Disclaimer

Please note, failure to select the correct materials or products we supply ("the Products") may result in damage to plant, equipment or property. In some instances, it may cause death or personal injury. We are not designers and do not give advice about design related matters concerning the Products. We can help and assist with the technical specifications for the Products. In specific applications, particularly where critical conditions exist, we will try to assist you within the limitations of the services that we offer. All information supplied by us is intended as technical co-operation outlining the specifications of the different Products which we supply. To the extent permitted in law, no warranty is given in respect of any information supplied by us. The customer must satisfy themselves as to the suitability of the Products for their intended application and use. The correct fitting of Products is the responsibility of the customer. Your statutory rights remain unaffected. Save in respect of death, personal injury or fraud, our entire liability to you, however arising from the supply of Products shall be limited to the £10M indemnity amount provided by our insurers.

Since all properties, specifications and application parameters shown throughout this catalogue are approximate and may be mutually influenced, your specific application should not be undertaken without independent study and evaluation for suitability. All technical data and advice given is based on experiences TEADIT® has made so far. Failure to select proper sealing products can result in damage and/or personal injury. Properties, specifications and application parameters are subject to change without notice. TEADIT® does not undertake any liability of any kind whatsoever. Please note: the color of the actual product might vary from the above image on this data-sheet.