



## Product information

REV202111

# Stuffing-Box-Packing Type 2007

## Description

Diagonally braided from pure, expanded PTFE-yarn with incorporated graphite, lubricated with silicone oil.

## Properties

The suppleness, chemical resistance, low coefficient of friction and excellent heat dissipation properties of PTFE/graphite make **TEADIT style 2007 one of the most widely used and most versatile packings in the market. WRAS approval.**

## Application areas

Very versatile pump packing, can also be used for valves, mixers, agitators, etc. **Style 2007 is particularly well suited for service involving high peripheral speeds and temperatures, where pure PTFE packings fail.**

## Application media


Can be safely used for almost all chemical applications including the most aggressive ones.

## Not suitable for

Highly oxidizing media like oleum, fuming nitric acid, aqua regia, gaseous fluorine, lacquer and paints.

## Benefits

**TEADIT style 2007 can - because of its extremely wide range of applications - successfully replace many other packings and reduce stock inventories considerably. This packing has been - after extensive testing over a long period - approved by Sunds Defibrators in Sweden for use in their refiners and similar equipment for the pulp- and paper industry. WRAS approval for potable water.**



### Temperature:

	- temp	+ temp
(°C)	200	280

### Pressure:

	rotating:	reciprocating:	static:
(bar)	35	100	200

pH: 0-14    density: (g/cm<sup>3</sup>) 1,7    v: (m/s) 25

### Approvals:

- WRAS

### Disclaimer

Please note, failure to select the correct materials or products we supply ("the Products") may result in damage to plant, equipment or property. In some instances, it may cause death or personal injury. We are not designers and do not give advice about design related matters concerning the Products. We can help and assist with the technical specifications for the Products. In specific applications, particularly where critical conditions exist, we will try to assist you within the limitations of the services that we offer. All information supplied by us is intended as technical co-operation outlining the specifications of the different Products which we supply. To the extent permitted in law, no warranty is given in respect of any information supplied by us. The customer must satisfy themselves as to the suitability of the Products for their intended application and use. The correct fitting of Products is the responsibility of the customer. Your statutory rights remain unaffected. Save in respect of death, personal injury or fraud, our entire liability to you, however arising from the supply of Products shall be limited to the £10M indemnity amount provided by our insurers.

Since all properties, specifications and application parameters shown throughout this catalogue are approximate and may be mutually influenced, your specific application should not be undertaken without independent study and evaluation for suitability. All technical data and advice given is based on experiences TEADIT® has made so far. Failure to select proper sealing products can result in damage and/or personal injury. Properties, specifications and application parameters are subject to change without notice. TEADIT® does not undertake any liability of any kind whatsoever. Please note: the color of the actual product might vary from the above image on this data-sheet.