



Product information

REV202111

Stuffing-Box-Packing Type 2024

Description

TEADIT style 2024 is an extruded packing made from pure PTFE-fine-powder and a food approved lubricant. Available in round cross section dimensions. Other cross sections available on request.

Properties

Style 2024 is a soft and dense packing. It has a very low coefficient of friction, excellent resistance to gas permeation and is self-lubricating. Style 2024 remains soft and pliable even after long service, which reduces friction on shafts and spindles. Can be used in areas where the naturally dark colour of TEADIT style 2022 is unsuitable, i.e. in the food and pharmaceutical industry.

Application areas

Suitable for use in pumps, mixers, sliders, valves, but also many static applications. Because of the softness of the packing, it is normally installed with a braided top and bottom ring.

Depending on the prevailing pressure and medium, TEADIT styles 2422, 2044, 2005 or 2006 can be recommended for this purpose.

Application media

Because of the exceptional chemical resistance of pure PTFE, style 2024 can be used with most substances, both liquid and gaseous. Also suitable for use with abrasive and crystallizing media.

Not suitable for

Alkali metals, fluorine and fluorine compounds at high temperature and pressure, oxygen.

Benefits

Style 2024 has a very low coefficient of friction and does therefore not damage shafts or spindles. Abrasive or crystallizing particles get embedded in the body of this packing. Can be used with a wide variety of different media, also for static applications.



Temperature:

- temp + temp
(°C) 100 250

Pressure:

rotating: reciprocating: static:
(bar) 10 20

pH: 0-14 density: (g/cm³) 1,90 v: (m/s) 4

Disclaimer

Please note, failure to select the correct materials or products we supply ("the Products") may result in damage to plant, equipment or property. In some instances, it may cause death or personal injury. We are not designers and do not give advice about design related matters concerning the Products. We can help and assist with the technical specifications for the Products. In specific applications, particularly where critical conditions exist, we will try to assist you within the limitations of the services that we offer. All information supplied by us is intended as technical co-operation outlining the specifications of the different Products which we supply. To the extent permitted in law, no warranty is given in respect of any information supplied by us. The customer must satisfy themselves as to the suitability of the Products for their intended application and use. The correct fitting of Products is the responsibility of the customer. Your statutory rights remain unaffected. Save in respect of death, personal injury or fraud, our entire liability to you, however arising from the supply of Products shall be limited to the £10M indemnity amount provided by our insurers.

Since all properties, specifications and application parameters shown throughout this catalogue are approximate and may be mutually influenced, your specific application should not be undertaken without independent study and evaluation for suitability. All technical data and advice given is based on experiences TEADIT® has made so far. Failure to select proper sealing products can result in damage and/or personal injury. Properties, specifications and application parameters are subject to change without notice. TEADIT® does not undertake any liability of any kind whatsoever. Please note: the color of the actual product might vary from the above image on this data-sheet.