

Product information

sealing for a safer and greener tomorrow

REV2013344

Stuffing-Box-Packing Type 3110

Material composition

TEADIT style 3110 is a braided tube - folded flat to form a tape - from pure expanded, flexible graphite.

Please note: the colour of the actual product might vary from the above image on this data-sheet.

Properties

Style 3110 is a very versatile gasket material for static applications. It has excellent temperature resistance and can be used with a wide variety of media. It comes in the following different cross-sections:

15 x 4mm, 25 x 3mm, 20 x 4mm, 30 x 4,5mm, 40 x 5mm, 25 x 6mm and 50 x 6mm.

Available with or without adhesive backing. Also available with Inconel reinforcement as style 3110/I.

Application areas

Static seal for metallic and non-metallic flanges, lids, covers, hatches, reactors, autoclaves, heaters, etc.

Application media

Suitable for most media in a wide variety of processes, including steam, fuel, gases, mineral and synthetic oils, effluents, condensate, process water, etc.

Not suitable for

Highly oxidizing media.

Benefits

Will easily form an endless seal. Because of the suppleness of the expanded graphite, style 3110 will conform perfectly to any dimension and shape.

Easy and quick to install. Can be used throughout a plant because of extremely high thermal and chemical resistance. Also available with adhesive backing for easy application to sealing surface.



Temperature:

	- temp	+ temp	steam:	inert gas:	
(°C)	240	450	650	1000	
Pressure: rotating: reciprocating: static:					
· (bar)			300		
; pH: (pH: 0-14 density: 1		v: (m/s)		



WILLIAM JOHNSTON & COMPANY LIMITED

TEL: +44 (0) 141 620 1666 I

email: sales@williamjohnston.co.uk

www.williamjohnston.co.uk

Since all properties, specifications and application parameters shown throughout this catalogue are approximate and may be mutually influenced, your specific application should not be undertaken without independent study and evaluation for suitability. All technical data and advice given is based on experiences TEADIT® has made so far. Failure to select proper sealing products can result in damage and/or personal injury. Properties, specifications and application parameters are subject to change without notice. TEADIT® does not undertake any liability of any kind whatsoever. Please note: the colour of the actual product might vary from the above image on this data-sheet.