



Product information

REV2013344

Stuffing-Box-Packing Type 2777

Material composition

Diagonally braided from synthetic yarn (Novoloid), impregnated with PTFE-dispersion and a silicone free lubricant.

Please note: the colour of the actual product might vary from the above image on this data-sheet.

Properties

Excellent general service pump and valve packing, Teadit style 2777 is very pliable and conforms readily to stuffing box configurations, installs easily and needs only minimal gland torque and few adjustments. Covers a wide variety of applications in many industries.

Application areas

Teadit style 2777 can be used in most pump and valve applications in the chemical industry, pulp- and paper mills, marine service and many more.

Application media

Teadit style 2777 covers a pH range from 1 - 13 and can be used with water, brine, steam, acids, lyes, chemicals, solvents, liquors, oils and greases, etc.

Not suitable for

Concentrated or hot sulphuric- (>60%) and nitric acid (>10%), highly concentrated alkalis.

Benefits

Very flexible and hard-wearing all-round packing, does not harden and is not abrasive (no shaft wear), no electrolytic pitting, non-contaminating (does not leach colour), high extrusion resistance.



Temperature:

	- temp	+ temp
(°C)	100	250

Pressure:

	rotating:	reciprocating:	static:
(bar)	25	50	100

pH: 1-13 density: 1,3 v: (m/s) 15



STOCKED, SUPPORTED AND DISTRIBUTED BY



WILLIAM JOHNSTON
& COMPANY LIMITED

TEL: +44 (0) 141 620 1666

email: sales@williamjohnston.co.uk

www.williamjohnston.co.uk

TEADIT INT. - Rosenheimer Str. 10, 6330 Kufstein, AUSTRIA, Tel.: +43-5372-64020-0, Fax: +43-5372-64020-20, austria@teadit.eu, www.teadit.eu
TEADIT Deutschland - Schanzenstr. 35, 51063 Köln, GERMANY, Tel.: +49-221-922 342-0, Fax: +49-221-922 342-22, germany@teadit.eu

Since all properties, specifications and application parameters shown throughout this catalogue are approximate and may be mutually influenced, your specific application should not be undertaken without independent study and evaluation for suitability. All technical data and advice given is based on experiences TEADIT® has made so far. Failure to select proper sealing products can result in damage and/or personal injury. Properties, specifications and application parameters are subject to change without notice. TEADIT® does not undertake any liability of any kind whatsoever. Please note: the colour of the actual product might vary from the above image on this data-sheet.