

## TECHNICAL DATA



# WILLIAM JOHNSTON & COMPANY LIMITED



Inverness +44 (0) 1463 238 673 ☀ Head Office +44 (0) 141 620 1666 (8 lines) ☀ Ashford +44 (0) 1233 330 766  
[sales@williamjohnston.co.uk](mailto:sales@williamjohnston.co.uk) ☀ [www.williamjohnston.co.uk](http://www.williamjohnston.co.uk)

### PRODUCT NAME

**Commercial EPDM 60**

### DESCRIPTION

High grade EPDM suitable for applications where good ozone and weather resistance is required. Also suitable for some mineral oils

### THICKNESS (mm)

1mm - 25mm

### SHEET SIZE (M)

1.4M X 5M, 10M & 20M -thickness dependant

### FINISH

Plate/Plate

### MATERIAL

EPDM

### APPLICATION

General Purpose

### INSERTION

No

### CHEMICAL RESISTANCE

*PLEASE REFER TO OUR CHEMICAL DATA SHEET*

SPECIFICATIONS COMPOUND	Values [typical]
COLOUR	Black
COMPOUND	EPDM
DENSITY [SPECIFIC GRAVITY] g/cm <sup>3</sup>	1.15
HARDNESS [DEGREES SHORE A] +/-5	60
TENSILE STRENGTH MPa	10
ELONGATION AT BREAK %	300
MINIMUM TEMPERATURE °C	-30
MAXIMUM TEMPERATURE °C	+130
COMPRESSION SET (70°C 22 hours) %	30

*As the companies' products are used in multiple applications and as the company has no control over the method of their use, the company excludes all conditions or warranties, expressed or implied by statute or otherwise. Any technical co-operation is given for customers' assistance only and without liability on the part of the company.*