



**WILLIAM JOHNSTON
& COMPANY LIMITED**



Glasgow Tel: +44 (0) 141 620 1666 | Inverness Tel: +44 (0) 1463 238 673
sales@williamjohnston.co.uk | www.williamjohnston.co.uk

PRODUCT NAME

Commercial EPDM 60

DESCRIPTION

High grade EPDM suitable for applications where good ozone and weather resistance is required. Also suitable for some mineral oils

THICKNESS (mm)

1mm - 25mm

SHEET SIZE (M)

1.4M X 5M, 10M & 20M -thickness dependant

FINISH

Plate/Plate

MATERIAL

EPDM

APPLICATION

General Purpose

INSERTION

No

CHEMICAL RESISTANCE

PLEASE REFER TO OUR CHEMICAL DATA SHEET

SPECIFICATIONS COMPOUND	Values [typical]
COLOUR	Black
COMPOUND	EPDM
DENSITY [SPECIFIC GRAVITY] g/cm³	1.15
HARDNESS [DEGREES SHORE A] +/-5	60
TENSILE STRENGTH MPa	10
ELONGATION AT BREAK %	300
MINIMUM TEMPERATURE °C	-30
MAXIMUM TEMPERATURE °C	+130
COMPRESSION SET (70°C 22 hours) %	30

As the companies' products are used in multiple applications and as the company has no control over the method of their use, the company excludes all conditions or warranties, expressed or implied by statute or otherwise. Any technical co-operation is given for customers' assistance only and without liability on the part of the company.