



**WILLIAM JOHNSTON
& COMPANY LIMITED**



Glasgow Tel: +44 (0) 141 620 1666 | Inverness Tel: +44 (0) 1463 238 673
sales@williamjohnston.co.uk | www.williamjohnston.co.uk

PRODUCT NAME

BS1154 Z40

DESCRIPTION

A black 40 degree shore A hardness natural rubber fully tested to British Standard BS1154. Used in high performance applications where tensile strength and abrasion resistance are required.

THICKNESS (mm)

1.5, 2.0, 3.0, 5.0, 6.0, 12.0

SHEET SIZE (M)

Length 20M (1.5mm,2.0mm)
 Length 10M (2.5mm - 6.0mm)
 Length 5M (8.0 mm - 25.0mm)

FINISH

plate

MATERIAL

Natural BS1154 Z40

APPLICATION

Where good abrasion, tensile strength, Ozone and UV resilience are required

INSERTION

NO

CHEMICAL RESISTANCE

PLEASE REFER TO OUR CHEMICAL DATA SHEET

SPECIFICATIONS COMPOUND	Values [typical]
COLOUR	BLACK
COMPOUND	NATURAL
DENSITY [SPECIFIC GRAVITY] g/cm³	1.10
HARDNESS [DEGREES SHORE A] +/-5	40
TENSILE STRENGTH MPa	19.0
ELONGATION AT BREAK %	600
MINIMUM TEMPERATURE °C	-20
MAXIMUM TEMPERATURE °C	+70
ABRASION RESISTANCE mm³	110

Failure to select the correct materials or products can result in damage to plant and equipment and personal injury. In specific applications, particularly where critical conditions exist, we suggest you contact us and we will consider with you the most suitable material or product. However, information supplied by William Johnston & Company Limited is intended only as technical co-operation and as a guide to the various uses of different products. No warranty is given in respect of information or recommendations by William Johnston & Company Limited which are only given for guidance and without any guarantee. The customer must satisfy themselves on the suitability of the material or product for the intended purpose. The correct fitting of products is the responsibility of the customer.