TECHNICAL DATA





Glasgow Tel: +44 (0) 141 620 1666 | Inverness Tel: +44 (0) 1463 238 673 sales@williamjohnston.co.uk Т

www.williamjohnston.co.uk

PRODUCT NAME

DESCRIPTION

BS2752 C60

A high grade pure CR (Chloroprene Rubber) manufactured under strict control to BS2752/C40 specification. Good resistance to Weathering, Ozone, Salt Water and some Greases. Selfextinguishing. 0.5 to 6

1.4 x 10

Plate/plate

Chloroprene BS2752 C60

Good resistance to Weathering, Ozone, Salt Water and some Greases. Self-extinguishing. NO

PLEASE REFER TO OUR CHEMICAL DATA SHEET

SPECIFICATIONS COMPOUND	Values [typical]
COLOUR	BLACK
COMPOUND	CHLOROPRENE
DENSITY [SPECIFIC GRAVITY] g/cm	³ 1.40
HARDNESS [DEGREES SHORE A] +/-:	5 60
TENSILE STRENGTH MP	a 13.0
ELONGATION AT BREAK	⁶ 350
MINIMUM TEMPERATURE	-30
MAXIMUM TEMPERATURE	C <mark>+120</mark>
COMPRESSION SET (70°C/22 Hrs) 9	⁶ 25

Failure to select the correct materials or products can result in damage to plant and equipment and personal injury. In specific applications, particularly where critical conditions exist, we suggest you contact us and we will consider with you the most suitable material or product. However, information supplied by William Johnston & Company Limited is intended only as technical co-operation and as a guide to the various uses of different products. No warranty is given in respect of information or recommendations by William Johnston & Company Limited which are only given for guidance and without any guarantee. The customer must satisfy themselves on the suitability of the material or product for the intended purpose. The correct fitting of products is the responsibility of the customer.

THICKNESS (mm) SHEET SIZE (M) FINISH MATERIAL APPLICATION

INSERTION CHEMICAL RESISTANCE