



**WILLIAM JOHNSTON  
& COMPANY LIMITED**



Glasgow Tel: +44 (0) 141 620 1666 | Inverness Tel: +44 (0) 1463 238 673  
[sales@williamjohnston.co.uk](mailto:sales@williamjohnston.co.uk) | [www.williamjohnston.co.uk](http://www.williamjohnston.co.uk)

**PRODUCT NAME**

**Commercial Neoprene 60**

**DESCRIPTION**

A black 60 shore A hardness Chloroprene rubber used in a wide variety of applications. A good general all purpose elastomer with low oil and moderate ozone resistance yet good compression set

**THICKNESS (mm)**

1, 1.5, 3.0, 6.0

**SHEET SIZE (M)**

1.4 x 10

**FINISH**

Plate

**MATERIAL**

Chloroprene

**APPLICATION**

Good strength, abrasion resistance. Resistant to weathering, ageing, acids, salts, ozone, fats, animal/vegetable oil. Not suited to aromatic hydrocarbons and ketones

**INSERTION**

No

**CHEMICAL RESISTANCE**

*PLEASE REFER TO OUR CHEMICAL DATA SHEET*

SPECIFICATIONS COMPOUND	Values [typical]
COLOUR	Black
COMPOUND	Chloroprene/Styrene Butadiene
DENSITY [SPECIFIC GRAVITY] g/cm <sup>3</sup>	1.5
HARDNESS [DEGREES SHORE A] +/-5	60
TENSILE STRENGTH MPa	3
ELONGATION AT BREAK %	250
MINIMUM TEMPERATURE °C	-20
MAXIMUM TEMPERATURE °C	+70 (90 intermittent)
COMPRESSION SET 70 DEG 22 HRS %	35

*As the companies' products are used in multiple applications and as the company has no control over the method of their use, the company excludes all conditions or warranties, expressed or implied by statute or otherwise. Any technical co-operation is given for customers' assistance only and without liability on the part of the company.*