**TECHNICAL DATA** 





WILLIAM JOHNSTON & COMPANY LIMITED

Inverness +44 (0) 1463 238 673 Head Office +44 (0) 141 620 1666 (8 lines) Ashford +44 (0) 1233 330 766 <u>sales@williamjohnston.co.uk</u> www.williamjohnston.co.uk

**PRODUCT NAME** 

## BS2751 BA60

DESCRIPTION

A high grade pure NBR (acrylonitrile butadeine) manufactured under strict control to BS2751/BA60 specification. Oils, fuels, greases & water. Excellent physical and mechanical properties. 1 to 6

1.4 x 10

Plate/plate

Nitrile BS2751

Chemical resistance, oil, fuel, weather, Ozone.

PLEASE REFER TO OUR CHEMICAL DATA SHEET

SPECIFICATIONS COMPOUND	Values [typical]	-
COLOUR	BLACK	
COMPOUND	NBR	2.1
DENSITY [SPECIFIC GRAVITY] g/c	m <sup>3</sup> 1.40	
HARDNESS [DEGREES SHORE A] +	/-5 60	
TENSILE STRENGTH M	Pa 13.0	
ELONGATION AT BREAK	%400	
MINIMUM TEMPERATURE	°C-30	300
MAXIMUM TEMPERATURE	°C+120	
ABRASION RESISTANCE m	m <sup>3</sup> 160	
TEAR RESISTANCE Kg/c	cm N/A	-

Failure to select the correct materials or products can result in damage to plant and equipment and personal injury. In specific applications, particularly where critical conditions exist, we suggest you contact us and we will consider with you the most suitable material or product. However, information supplied by William Johnston & Company Limited only as technical co-operation and as a guide to the various uses of different products. No warranty is given in respect of information or recommendations by William Johnston & Company Limited which are only given for guidance and without any guarantee. The customer must satisfy themselves on the suitability of the material or product for the intended purpose. The correct fitting of products is the responsibility of the customer.

THICKNESS (mm) SHEET SIZE (M) FINISH MATERIAL APPLICATION INSERTION CHEMICAL RESISTANCE