## TECHNICAL DATA





Glasgow Tel: +44 (0) 141 620 1666 I Inverness Tel: +44 (0) 1463 238 673 <u>sales@williamjohnston.co.uk</u> I <u>www.williamjohnston.co.uk</u>

PRODUCT NAME BS2751 BA70

DESCRIPTION A high grade pure NBR (acrylonitrile butadeine)

manufactured under strict control to

BS2751/BA70 specification. Oils, fuels, greases

& water. Excellent physical and mechanical

properties.

THICKNESS (mm) 1 to 6

SHEET SIZE (M)  $1.4 \times 10$ 

FINISH Plate/plate

MATERIAL Nitrile BS2751

APPLICATION Chemical resistance, oil, fuel, weather, Ozone.

INSERTION

CHEMICAL RESISTANCE PLEASE REFER TO OUR CHEMICAL DATA

SHEET

SPECIFICATIONS COMPOUND	Values [typical]
COLOUR	BLACK
COMPOUND	NBR
DENSITY [SPECIFIC GRAVITY] g/d	cm <sup>3</sup> 1.4
HARDNESS [DEGREES SHORE A] +	-/-5 70
TENSILE STRENGTH M.	1Pa 13.0
ELONGATION AT BREAK	% 350
MINIMUM TEMPERATURE	°C -30
MAXIMUM TEMPERATURE	°C +120
ABRASION RESISTANCE m	nm <sup>3</sup> 160
TEAR RESISTANCE Kg/	/cm <b>N/A</b>

Failure to select the correct materials or products can result in damage to plant and equipment and personal injury. In specific applications, particularly where critical conditions exist, we suggest you contact us and we will consider with you the most suitable material or product. However, information supplied by William Johnston & Company Limited is intended only as technical co-operation and as a guide to the various uses of different products. No warranty is given in respect of information or recommendations by William Johnston & Company Limited which are only given for guidance and without any guarantee. The customer must satisfy themselves on the suitability of the material or product for the intended purpose. The correct fitting of products is the responsibility of the customer.