



WILLIAM JOHNSTON

& COMPANY LIMITED

Glasgow Tel: +44 (0) 141 620 1666 | Inverness Tel: +44 (0) 1463 238 673
sales@williamjohnston.co.uk | www.williamjohnston.co.uk

PRODUCT NAME	SNOWPLOUGH RUBBER
DESCRIPTION	COMPOUNDED GRADE OF SBR WITH FABRIC BACKING. DEISGND FOR HIGH ABRASION RESISTANCE
THICKNESS (mm)	12.0, 15.0, 20.0, 25.0
SHEET SIZE	1.4M x 5M
FINISH	PLATE/PLATE
MATERIAL	SBR
APPLICATION	EXTREMELY HIGH ABRASION BUT WITH LIMITED CHEMICAL, OZONE, UV & OIL RESISTANCE PERFORMANCE
INSERTION	NO
CHEMICAL RESISTANCE	PLEASE REFER TO OUR CHEMICAL DATA SHEET

SPECIFICATIONS	Values
COMPOUND	(Typical)
COLOUR	BLACK
COMPOUND	SBR
DENSITY (SPECIFIC GRAVITY) g/cm³	1.15
HARDNESS (DEGREES SHORE A) +/-	80
TENSILE STRENGTH MPa	11.0
ELONGATION AT BREAK %	350
MINIMUM TEMPERATURE °C	-20
MAXIMUM TEMPERATURE °C	+700

Failure to select the correct materials or products can result in damage to plant and equipment and personal injury. In specific applications, particularly where critical conditions exist, we suggest you contact us and we will consider with you the most suitable material or product. However, information supplied by William Johnston & Company Limited is intended only as technical co-operation and as a guide to the various uses of different products. No warranty is given in respect of information or recommendations by William Johnston & Company Limited which are only given for guidance and without any guarantee. The customer must satisfy themselves on the suitability of the material or product for the intended purpose. The correct fitting of products is the responsibility of the customer.